



When precision matters.™

TW3101 Non Magnetic GPS L1 Antenna


The TW3101 by Tallysman Wireless is a precision grade, permanent mount GPS L1 antenna with no magnetic properties, specially designed to be used in close proximity with compass based instruments.

The TW3101 features a custom high performance, dual-feed, wide band patch element. Its LNA configuration provides a LNA for each feed, a mid section high rejection SAW for the combined signal, followed by a final stage of LNA. It provides ± 10 MHz bandwidth centred on 1575.42 MHz and covers all GPS L1 and SBAS (WAAS/EGNOS/MSAS) signals. It features great axial ratio over the entire frequency range (< 3 dB), excellent circular polarized signal reception, great multipath rejection and out-of-band signal rejection.

The TW3101 is housed in a permanent mount industrial-grade weather-proof enclosure and two options for pole mounting are available an L-bracket (P/N#23-0040-0) or a pipe mount (P/N#23-0065-0).



TW3101 Dimensions (mm)
Low Profile Radome shown. Conical Radome also available



Applications

- Inertial Navigation (IMU) Systems
- Compass based Systems
- Heading Reference Systems
- Military & Security
- Precision Tracking & Navigation
- Machine Control Systems

Features

- Non magnetic composition
- Great axial ratio: 1 dB typ., 3 dB max
- Low noise LNA: 1 dB
- High rejection SAW filter
- High gain: 28 dB typ.
- Low current: 14 mA typ.
- ESD circuit protection: 15 KV
- Weather proof housing: IP67

Benefits

- No compass interference
- Excellent multipath rejection
- Increase system accuracy
- Excellent signal to noise ratio
- Great out of band signal rejection
- Ideal for harsh environments
- RoHS compliant



When precision matters...™

TW3101 Non Magnetic GPS L1 Antenna

Specifications $V_{cc} = 3V$, over full bandwidth, $T=25^{\circ}C$

Antenna

Architecture	Dual, Quadrature Feeds
Antenna Element Gain (100mm ground plane)	4.25 dBic at 90°
Axial Ratio (over full bandwidth)	1dB typ., 3 dB max

Electrical

Architecture	One LNA per feed line, mid section SAW filter
Frequency Bandwidth	1575 MHz \pm 10 MHz
Polarization	RHCP
Gain	28 dB min. (at 1575.42 MHz)
Out-of-Band Rejection	<1560 MHz >42 dB >1600 MHz >31 dB >1620 MHz >45 dB
VSWR (at LNA input)	<1.5:1 typ. 1.8:1 max.
Noise Figure	1 dB typ.
Supply Voltage Range	+2.5 to 16 VDC nominal
Supply Current	14 mA typ., 20mA max
ESD Circuit Protection	15 KV air discharge

Mechanicals & Environmental

Properties	Non Magnetic
Mechanical Size	66.5 mm dia. x 21mm H
Operating Temp. Range	-40 to +85 °C
Enclosure	Radome: EXL9330, Base: Zamak White Metal
Weight	150 g
Attachment Method	18mm/M18 mast or 19mm bracket mount
Environmental	IP67 and RoHS compliant
Shock	Vertical axis: 50 G, other axes: 30 G
Vibration	3 axis, sweep = 15 min, 10 to 200 Hz sweep: 3 G
Warranty	One year – parts and labour

Ordering Information

Product Number:	TW3101 – NonMagnetic GPS L1 Antenna	33-3101-xx-yy-zzzz
-----------------	-------------------------------------	--------------------

Where xx = connector type, yy = type and colour of radome and zzzz = cable length in mm (where applicable)
Please refer to the Ordering Guide (<http://www.tallysman.com/orderingguide.php>) for the current and complete list of available radomes and connectors.

Tallysman Wireless Inc

36 Steacie Drive
Ottawa ON K2K 2A9 Canada Tel 613 591 3131 Fax 613 591 3121
sales@tallysman.com

The information provided herein is intended as a guide only and is subject to change without notice. This document is not to be regarded as a guarantee of performance. Tallysman Wireless Inc. hereby disclaims any or all warranties and liabilities of any kind. © 2010 Tallysman Wireless Inc. All rights reserved. Rev 2.4